



DPA616

Sixteen-channel Class-D amplifier 16 x 60W

Highlights:

- Lightweight class-D amplifier
- Stereo & bridged mode
- Terminal block output connections
- Advanced DSP and loudspeaker management
- 16 Channel design (8 channel bridged)



Product information:

The DPA616 is a professional sixteen channel power amplifier which is capable of delivering a power of 60 Watt to 4 Ohm loads connected to the 16 output channels. When used in bridge mode, it can deliver a power of 120 Watt to 8 Ohm loads connected to the 8 bridged outputs. This way, the DPA616 is the perfect solution for installed multi-zone audio distribution systems with 8 or 16 zones. This amplifier is designed as a no-nonsense amplifier with only the necessary controls and connections which creates great simplicity in use and installation. The input connections are all performed with 3-pin Terminal block connectors, allowing the connection of balanced input signals. Every channel is fitted with a separate gain control potentiometer and for every two input connectors, there is a stereo / bridge & parallel switch provided whereby two channels can be bridged or linked in parallel, avoiding a cable clutter when multiple channels should be fed with the same input signal. The output connections are performed with 4-pin Terminal block connectors allowing connections for separate or bridged output channels. A built-in multipurpose protection circuit protects against DC malfunction, short circuit, overheating, overload and limits the signal when necessary. This all is housed in a double rack space, steel 19" rack mount housing.

Applications:

- Bars, restaurants
- Public facilities
- Corporate spaces

System specifications:

RMS Power	@ 4 Ω Stereo	16 x 60 W
	@ 8 Ω Stereo	16 x 30 W
	@ 8 Ω Bridge	8 x 120 W
Frequency	Response (\pm 3 dB)	20 Hz - 20 kHz
Signal / Noise		> 100 dB
THD+N (@ 1 kHz)		< 0.1%
Technology		Class-D
Inputs	Sensitivity (1W/1m)	-20 dB ~ +20 dB
	Connector	3-pin Euro Terminal Block (Pitch - 3.81 mm)
Outputs	Connector	4-pin Euro Terminal Block (Pitch - 5.08 mm)
Power	Supply	Switching mode
	Source	100 ~ 240 V AC / 50 ~ 60 Hz
Protection		DC Short circuit
		Over heating
		Over load
		Signal limiting
Operating temperature		0° ~ 40° @ 95% Humidity

Product Features:

Dimensions	482 x 88 x 322 mm (W x H x D)
Weight	8.200 kg
Mounting	19"
Unit height	2 HE
Construction	Steel
Colours	Black